

# Sliding Control Modes.

Enric Fossas Colet



Institut d'Organització i Control  
de Sistemes Industrials



UNIVERSITAT POLITÈCNICA DE CATALUNYA



- To show a domain in the frontier between “*applied mathematics*” and “*engineering*”.

- To show a domain in the frontier between “*applied mathematics*” and “*engineering*”.
- *How?* Through a course in control, in particular a course in *Sliding Control Modes*.



## 📍 Lecture 1.

- 📍 What is control?
- 📍 Variable Structure Systems. Sliding Control Modes.
- 📍 Real and ideal sliding modes.
- 📍 The uniqueness problem.
- 📍 Designing controllers.


## 🔵 Lecture 1.

- 🔵 What is control?
- 🔵 Variable Structure Systems. Sliding Control Modes.
- 🔵 Real and ideal sliding modes.
- 🔵 The uniqueness problem.
- 🔵 Designing controllers.

## 🔵 Lecture 2


- 🔵 Definitions. Problems.
- 🔵 The equivalent control method.
- 🔵 The Ideal Sliding Dynamics.
- 🔵 Single Input Single Output Systems (existence).

### Lecture 3





-  Examples: a linear system of relative degree 2, a non-minimum phase nonlinear system of relative degree 1, a time dependent sliding surface.



### Lecture 3

-  Examples: a linear system of relative degree 2, a non-minimum phase nonlinear system of relative degree 1, a time dependent sliding surface.

### Lecture 4

-  Multi Input Multi Output Systems (existence).
-  A Lyapunov Theorem.
-  An example to be careful.
-  From MIMO to SISO, decoupling inputs and outputs.

## ● Lecture 3

- Examples: a linear system of relative degree 2, a non-minimum phase nonlinear system of relative degree 1, a time dependent sliding surface.

## ● Lecture 4

- Multi Input Multi Output Systems (existence).
- A Lyapunov Theorem.
- An example to be careful.
- From MIMO to SISO, decoupling inputs and outputs.

## ● Lectures 5 and 6

- Examples and exercises.




📍 **System:** A device or process having identifiable inputs and outputs.




- **System**: A device or process having identifiable inputs and outputs.
- **Inputs** can be either manipulated at will or be undesirable external influences. Undesirable, generally unpredictable and often unmeasurable inputs are called **disturbances**.

- 📍 **System**: A device or process having identifiable inputs and outputs.
- 📍 **Inputs** can be either manipulated at will or be undesirable external influences. Undesirable, generally unpredictable and often unmeasurable inputs are called **disturbances**.
- 📍 **Open** vs. **closed loop** systems.  
In an open loop control system, the input applied to the process under control does not depend on the actual output. In open-loop control there is no error correction.  
The severity of the disturbances determines which systems can operate under open-loop control. Regardless of disturbances, the ability to calibrate the system can determine whether or not open-loop control is applicable.











• A DC motor.




• A DC motor.



• State-space.

$$\frac{d}{dt} \begin{pmatrix} \dot{\theta} \\ i \end{pmatrix} = \begin{pmatrix} -\frac{b}{J} & \frac{K}{J} \\ -\frac{K}{L} & -\frac{R}{L} \end{pmatrix} \begin{pmatrix} \dot{\theta} \\ i \end{pmatrix} + \begin{pmatrix} 0 \\ \frac{1}{L} \end{pmatrix} v$$

• A DC motor.



• State-space.

$$\frac{d}{dt} \begin{pmatrix} \dot{\theta} \\ i \end{pmatrix} = \begin{pmatrix} -\frac{b}{J} & \frac{K}{J} \\ -\frac{K}{L} & -\frac{R}{L} \end{pmatrix} \begin{pmatrix} \dot{\theta} \\ i \end{pmatrix} + \begin{pmatrix} 0 \\ \frac{1}{L} \end{pmatrix} v$$

• Input-Output form.

$$\left. \begin{aligned} s(Js + b)\Theta(s) &= KI(s) \\ (Ls + R)I(s) &= V - Ks\Theta(s) \end{aligned} \right\} \Rightarrow \frac{\dot{\Theta}}{V} = \frac{K}{(Js + b)(Ls + R) + K^2}$$

(Clepsidra, Ctesibio  $\sim 300 - 270AC$ )

